



# Cellu-Cushion<sup>®</sup>-NS

Non-skid Polyethylene Foam

Ideal for high coefficient-of-friction or non-skid applications where holding components in place is required.



**Sealed Air Corporation**

# Cellu-Cushion®-NS Foam Benefits

## Cellu-Cushion®-NS Non-Skid Polyethylene Foam Provides...

- **Low Slip Surface** – Unique formulation provides a strong, flexible, and textured non-skid/low slip surface for holding delicate components, tools, or instruments in place during handling and transportation.
- **Durability** – Heavy density foam provides a strong foam material with excellent tensile and tear properties.
- **Flexibility** – Lightweight thin foam easily bends and flexes without breaking or cracking.
- **Patterns and Colors** – Available in red or black with embossed diamond or micro dot pattern.



## Cellu-Cushion®-NS Foam Applications

- Toolbox Liners
- Sliding Drawer Liners
- OEM Parts
- Workstation Surfaces/Mats
- Reusable Tote Liners/Inserts
- Athletic/Sporting Equipment
- Rug Underlayment
- Medical Applications
- Laptop/PC Work Areas
- Mouse Pads
- Coasters
- Others




| Property                            | ASTM Method            | Typical Values |           |
|-------------------------------------|------------------------|----------------|-----------|
|                                     |                        | 3/32"          | 1/8"      |
| Density                             | ASTM D3575-93          | 3 pcf          | 3 pcf     |
| Width (inches)                      |                        | 48"            | 48"       |
| Compression Strength (psi) @25%/50% | ASTM D3575-93 Suffix D | 4.5/15.0       | 5.5/15.5  |
| Tensile Strength (psi) md/cmd       | ASTM D3575-93 Suffix T | 160<br>85      | 120<br>65 |
| Tensile Elongation (%)              | ASTM D3575-93 Suffix T | 100            | 110       |
| Tear Resistance (lb./in.)           | ASTM D3575-93 Suffix G | 40             | 30        |

| Size               | Item   | Colors     | Sq. Ft. |
|--------------------|--------|------------|---------|
| 3/32" x 48" x 250' | NS 300 | Black, Red | 1000    |
| 1/8" x 48" x 250'  | NS 300 | Black, Red | 1000    |

Additional thicknesses, densities, and colors can be special ordered at volume to meet specific needs.

**Fabricated/Distributed by:**



**Sealed Air Corporation**

**Polyolefin Foam Division**

301 Mayhill Street, Saddle Brook, NJ 07663-5303  
1-800-648-9093, Fax: (201) 712-7070  
www.sealedair.com

**Our Products Protect Your Products®**

**CORPORATE HEADQUARTERS:** Park 80 East, Saddle Brook, NJ 07663  
**INTERNATIONAL:** Offices throughout North and South America, Europe, Africa, Asia and Australasia.

© Reg. U.S. Pat. Off. © Sealed Air Corporation 2002. All Rights Reserved.  
Printed in the U.S.A., 10% post consumer materials.

PFD# 3/02